

CoreLine waterproof

WT120C G3

Scan me!

Scan me!

Triangle hook 2x
Gland cable ring 2x
Bolt M3x40 2x
Nut M3 2x
Screw plug 2x
Gland PG13.5 1x

Service tag

Power

Lumen

Energy efficiency class of Light source

Emergency unit (optional)

Max. interconnected number

WT120C G3 20S/840 PSR MDUPHW L600	14	2170	C	No	0.87	*
WT120C G3 27S/840 PSR MDUPHW L1200	17	2700	C	Yes	1.34	*
WT120C G3 40S/840 PSR MDUPHW L1200	25	4000	C	Yes	1.34	*
WT120C G3 34S/840 PSR MDUPHW L1500	21.5	3400	C	Yes	1.70	*
WT120C G3 60S/840 PSR MDUPHW L1500	37.5	6000	C	Yes	1.70	*
WT120C G3 80S/840 PSR MDUPHW L1500	50	8000	C	Yes	1.70	*
WT120C G3 27S/840 PSR MDUPHW TW3 L1200	17	2700	C	Yes	1.49	73
WT120C G3 40S/840 PSR MDUPHW TW3 L1200	25	4000	C	Yes	1.49	53
WT120C G3 34S/840 PSR MDUPHW TW3 L1500	21.5	3400	C	Yes	1.90	61
WT120C G3 60S/840 PSR MDUPHW TW3 L1500	37.5	6000	C	Yes	1.90	35

*Refer to the datasheet for detailed information on through wiring options.

PSR

Type	Dimension (mm)						Nr of clips
	A	B	C	D	E min	E max	F
WT120C G3 L600	76	665	80	38	308	512	6
WT120C G3 L1200	76	1215	80	38	538	1062	10
WT120C G3 L1500	76	1515	80	38	838	1362	12

PSR TW3

Type	Dimension (mm)						Nr of clips
	A	B	C	D	E min	E max	F
WT120C G3 TW3 L1200	76	1235	80	38	538	1062	10
WT120C G3 TW3 L1500	76	1535	80	38	838	1362	12

1

1a

1b

1c

Vertical installation

Horizontal installation

2a

2b

2c

2d

2e

2f

2g

2h

2i

2j

3

4

5

Installation of Emergency unit (option with additional emergency module EM300V)

Emergency unit

Labels

Connection

Charge time

Emergency wiring

Emergency wiring

Emergency wiring

Emergency wiring

Emergency wiring

MDUPHW motion detection unit with wireless grouping

MDUPHW motion detection unit with wireless grouping

MDUPHW motion detection unit with wireless grouping

MDUPHW motion detection unit with wireless grouping

MDUPHW motion detection unit with wireless grouping

MDUPHW motion detection unit with wireless grouping

Configuration note

Configuration note

Sensor configuration by dip-switches & rotary dials

Sensor configuration by dip-switches & rotary dials

Dipswitch settings

Dipswitch settings

Dipswitch settings

Dipswitch settings

Dipswitch settings

Dipswitch settings

Dipswitch settings

Dipswitch settings

Stand-by dimming level

Stand-by dimming level

Rotary dials settings for wireless grouping

Rotary dials settings for wireless grouping

Transmitter setting

Transmitter setting

Receiver setting

Receiver setting

Wireless grouping note

Wireless grouping note

Application guidelines for wireless grouping

Application guidelines for wireless grouping

Application guidelines for wireless grouping

Application guidelines for wireless grouping

Application guidelines for wireless grouping

Application guidelines for wireless grouping

Power on behavior - initialization

Power on behavior - initialization

Sensor detection area

Sensor detection area

Ceiling mounting

Ceiling mounting

Ceiling mounting

Ceiling mounting

Ceiling mounting

Ceiling mounting

Ceiling mounting

Ceiling mounting

Ceiling mounting

Ceiling mounting

Ceiling mounted height: 6m

Ceiling mounted height: 6m

Ceiling mounted height: 6m

Ceiling mounted height: 6m

Ceiling mounted height: 6m

Ceiling mounted height: 6m

Ceiling mounted height: 6m

Ceiling mounted height: 6m

Ceiling mounted height: 6m

Ceiling mounted height: 6m

Ceiling mounted height: 6m

Ceiling mounted height: 6m

Ceiling mounted height: 6m

Ceiling mounted height: 6m

